



Walkaround Outline for the ODB DCL750TM25 Direct Drive Self-Contained Debris & Leaf Collection System

*High Power, High Capacity,
Simple, Robust,
Budget-Friendly*



- **High Power**
 - ✓ Proven 74 HP John Deere Tier 4 Engine
 - ✓ Robust, Reliable, Ready Support
- **High Capacity**
 - ✓ 25 Cubic Yard Self-Contained Hopper
- **Automotive-Style PTO Clutch**
 - ✓ Smooth and Safe Operation
- **Ball Bearings on Boom Swivel Shaft**
 - ✓ Smooth Handling.
 - ✓ Less Operator Fatigue
- **25" Shred Master™ Fan Impeller**
 - ✓ Greater compaction, less trips to dump
 - ✓ More curb miles cleaned per shift

*Only ODB's DCL750TM25 has these
premium features in this product class.*

SPECIFICATIONS: DCL750TM25

Trailer

- Bolted on Pintle Eye
- Axles: Heavy Duty Oil-Filled Leaf Spring (20,000LBS)
- Electric brakes w break away actuator
- Parking jack

Tires

- (8) 235/80R16E tires on steel wheels

Auxiliary engine

- 74 HP John Deere Tier 4
- Cool-Flow™ protective pleated and boxed radiator air screen, with tool free access
- Fuel tank 40 Gallon polyethylene

Fan / Impeller

- Direct drive
- 25" SHRED-MASTER™ Fan Standard
- Back plate protects bearings and shaft
- Self-clearing
- AR400 material
- Fans are robotically welded, stress relieved and statically and dynamically balanced

Clutch: PTO

- Automotive style; easy engage & disengage
- 2.25" shaft
- Easily adjustable

Fan housing

- Robotically welded
- Replaceable ¼" steel liners

Boom

- Ball Bearing Boom Hose Swivel, top & bottom
- Electric powered 12V boom
- Hydraulic single axis boom (up/down)
- 16" x 120" Urethane Vacuum Hose
- Steel nozzle

SPECIFICATIONS: DCL750TM25 (cont.)

Hopper Construction

- Heavy duty 12-gauge steel
- Hopper width 101.5"
- Regular perforated steel with mesh overlay vents

Rear Door

- Single side hinge door
- Manual operation
- Higher RPM faster dumping w/o fan
- Gear driven electric pump
- Dump angle 52 degrees
- LED type DOT w/ two amber flashers

Hoist

- 14,900 LB single stage cylinder, Lo-Boy® hoist
- Welded into frame